

27360 W. Muirfield Lane, Valencia • California 91355 (661) 295-0900 • (800) 221-6449

Section 1 - Product and Company Identification

Date of SDS: 06/01/1995 Review Date: 02/26/2018

Product Identification: Slick Fit Die Lube
Product Synonym: Wax release lubricant
Product Class/Use: Lubricating material
Company Name: Talladium, Incorporated
Company Address: 27360 West Muirfield Lane

Valencia, California 91355 United States of America

General Information Telephone: (661)-295-0900 **Emergency Telephone:** Not required by regulations.

Section 2 - Composition/Information on Ingredients

SUBSTANCE

CAS No.

Paraffin Oil

8042-47-5

These items are Non-Hazardous Materials as defined under the US OSHA Hazard Communication Standard (29CFR 1910.1200)

Section 3 - Hazards Identification, Including Emergency Overview

May cause irritation to the eyes and skin

Section 4 - First Aid Measures

Eyes: If contact occurs, flush eyes with water for at least 15minutes. If irritation develops, seek medical attention.

Skin: Wash with soap and water. If irritation occurs seek medical attention.

Inhalation: Remove to fresh air. If breathing becomes difficult, seek medical attention.

Ingestion: If swallowed seek medical attention.

Section 5 - Fire Fighting Measures

Material is non-flammable.

Extinguishing Media: Dry chemical, foam, or carbon dioxide.

Section 6 - Accidental Release Measures

Spill or Leak Procedures: Absorb with paper towel or absorbing material and place into waste container for disposal. Clean surface with soap and water.

Waste Disposal Method: Contains no hazardous substances, dispose in accordance with Local, State and Federal regulations.

Section 7 - Handling and Storage

Handling: Keep container closed when not in use.

Storage: Store in a cool dry area in tightly sealed container.

Slick Fit Die Lube Page 1



Section 8 - Exposure Controls & Personal Protection

Respiratory Protection: None normally required. For fumes use a NIOSH approved organic respirator

Eye Protection: Use NIOSH approved safety glasses with side shields

Skin: If sensitivity occurs rubber gloves may be uses

Protective Equipment: N/A

Section 9 - Physical & Chemical Properties

Boiling Point: Not determined **Odor:** Mild odor **Melting Point:** N/A **Solubility:** Soluble

Appearance: Clear liquid

Section 10 - Stability & Reactivity Data

Stability: StableIncompatibility: None KnownHazardous Decomposition Products: None knownPolymerization: Will not occur

Section 11 - Toxicological Information

No data available

Section 12 - Ecological Information

Non-hazardous to the environment

Section 13 - Disposal Considerations

Waste Disposal Methods: No special treatment required for small amounts of liquid. Follow all Federal, State, and Local regulations.

Section 14 - Transport Information

U.S. DOT Information: Non hazardous, not regulated.

Section 15 - Regulatory Information

This item is non-hazardous

Section 16 - Other Information

The information and recommendations above are believed to be accurate and represent the best information currently available to us. Information prepared to meet U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200. The person receiving the above material should make their own determination as to the suitability for their use. Talladium makes no warranty expressed or implied with respect to this information and assumes no liability resulting from its use.

Slick Fit Die Lube Page 2